

公司资质和证书

COMPANY QUALIFICATION AND CERTIFICATE



我们拥有 ISO9001:2015 的质量管理体系认证, 自主进出口经营权, 产品认证证书有 VDE、TUV、UL、CUL、CE、CB、CQC 等, 环保证书有 RoHS 检测、REACH 测试、PAHs (多环芳香烃)、Phthalates 邻苯二甲酸酯)、Halogen (卤素) 等, 专利发明和软著 16 余项和各种荣誉证书和奖牌。为全球化客户的产品保驾护航。

We have ISO9001:2015 quality management system certification, independent import and export business rights, product certification certificates including VDE, TUV, UL, CUL, CE, CB, CQC, environmental protection certificates including RoHS testing, REACH testing, PAHs (polycyclic aromatic hydrocarbons), Phthalates phthalates), Halogen (halogen), more than 16 patent inventions and soft books, and various honorary certificates and medals. Guarantee the products of global customers.

企业环境

ENTERPRISE ENVIRONMENT



车间使用面积达到 5000m², 办公室 500m², 实验室 200m², 净化车间面积 1200m², 仓库 1500m²。
The workshop covers an area of 5000m², office area of 500m², laboratory area of 200m², purification workshop area of 1200m² and warehouse area of 1500m².

企业优势

ENTERPRISE ADVANTAGES

01

实力工厂, 为世界 500 强提供产品和服务;

Powerful factory, providing products and services for the world's top 500;

02

专注外贸, 专业的技术和团队超 50 人;

Focus on foreign trade, with more than 50 professional technical and service teams;

03

接受定制开发和贴牌服务。

Accept customized development and OEM services.

为全球工业类客户和机电类企业提供一站式电容解决方案

PROVIDING ONE-STOP CAPACITOR SOLUTIONS FOR GLOBAL INDUSTRIAL CUSTOMERS AND ELECTROMECHANICAL ENTERPRISES



133 8241 6300



佛山市顺德区顺美莱电子实业有限公司
SMILER ELECTRONIC INDUSTRIAL CO.,LTD.

地址: 广东省佛山市顺德区北滘镇顺江社区三乐东路 28 号华智科创中心 12 栋
Address: Building 12, Huazhi Science and Technology Innovation Center, No. 28 Sanle East Road, Shunjiang Community, Beijiao Town, Shunde District, Foshan City, Guangdong Province

电话 Tel: 0086-757-22391590/1
手机 Mobile phone: 0086-18007576965
邮箱 E-mail: ari@sml-cap.cn
网址 Website: www.smlcapacitor.com

SMILER CAPACITOR 顺美莱电子实业

电容器定制专家

CAPACITOR CUSTOMIZATION EXPERT



量身定制
CUSTOMIZED



性价比高
COST-EFFECTIVE



质量保障
QUALITY ASSURANCE



持续服务
CONTINUOUS SERVICE

企业简介

COMPANY PROFILE

顺美莱公司成立于 2012 年 8 月, 经过十年奋斗, 公司已经从单一的以 CBB61/CBB60 为主的交流薄膜电容的生产、销售公司逐步转变为以新能源 (光伏、风能和电动汽车等)、工业类中高端薄膜电容为主和传统家电的交流电机启动、运转电容为辅的研-产-销全方位全覆盖的进出口企业。我们拥有国际领先的研发技术和生产设备, 拥有 ISO9001、VDE、TUV、CE、UL、CB、CQC 等质量体系认证和产品认证, 为全球工业类客户和机电类企业提供一站式电容解决方案。

SMILER Company was founded in August 2012. After ten years of struggle, the company has gradually transformed from a single production and sales company of AC film capacitors mainly based on CBB61/CBB60 to an import and export enterprise with full coverage of research, production and sales, mainly focusing on high-end film capacitors such as new energy (solar photovoltaic, wind energy, electric vehicles, etc.) and industrial products, supplemented by AC motor starting and operating capacitors of traditional household appliances. We have internationally leading R&D technology and production equipment, ISO9001, VDE, TUV, CE, UL, CB, CQC and other quality system certification and product certification, providing one-stop capacitor solutions for global industrial customers and electromechanical enterprises.



总经理 General manager

11+ 年
生产经验
PRODUCTION EXPERIENCE

5000+ m²
生产厂房
PRODUCTION PLANT

100+ 台
专业设备
EQUIPMENT

200+ K
日产量
DAILY PRODUCTION

佛山市顺德区顺美莱电子实业有限公司
SMILER ELECTRONIC INDUSTRIAL CO.,LTD.

主营产品介绍

INTRODUCTION TO MAIN PRODUCTS

- 环保节能
- 易安装
- 质量保障
- 寿命长



DETAILS
CREATE EXCELLENCE
细节 - 成就不凡

直流支撑电容

DC-LINK CAPACITOR



- 产品结构**
介质: 金属化聚丙烯薄膜;
外壳: 铝壳、塑壳或者胶带封装;
内部灌封: 树脂填充 (UL94 V-0);
- 特点**
应用于直流滤波电路中, 可替代电解电容;
等效串联电阻小, 能承受较大的纹波电流;
自感小, 有自愈性, 寿命长;
- 应用场合**
风能发电、太阳能发电用变频器上;
交通工具: 电动车和混合动力车;
焊接设备, 电梯, 电机驱动;
- Product Structure**
Medium: metallized polypropylene film;
Shell: aluminum shell, plastic shell, or tape;
Internal potting: resin filling (UL94 V-0);
- Features**
Used in DC-Link circuits, can replace electrolytic capacitor;
Low ESR, high ripple current handling capabilities;
Low Ls, Self-healing property, Long lifetime;
- Applications**
Used in inverters of wind power and solar power;
Transportation: EV or HEV;
Welders, Elevators, Motor Driver systems;

缓冲吸收电容

SNUBBER CAPACITOR



- 产品结构**
介质: 金属化聚丙烯薄膜;
外壳: 塑壳或者胶带封装;
内部灌封: 树脂填充 (UL94 V-0);
- 特点**
耐脉冲能力强;
具有优秀的自愈性;
优异的阻燃性能;
优秀的可靠性;
使用寿命长;
符合 ROHS 标准;
- 应用场合**
IGBT 缓冲吸收;
开关电源;
- Product Structure**
Medium: metallized polypropylene film;
Shell: Plastic shell or tape;
Internal potting: resin filling (UL94 V-0);
- Features**
High pulse intensity;
Good self-healing properties;
Excellent flame retardant ability;
High reliability;
Long useful life;
Comply with ROHS standards;
- Applications**
IGBT Snubbing;
Switch-mode power supplies;

交流滤波电容

AC FILTER CAPACITOR



- 产品结构**
介质: 金属化聚丙烯薄膜;
外壳: 铝壳封装, 塑料支架;
内部灌封: 树脂填充 (UL94 V-0);
- 特点**
可承受高的有效值电流;
可承受高频工作环境: Up to 20kHz;
可靠性高, 有自愈性, 寿命长;
- 应用场合**
逆变器、变频器上;
UPS 不间断电源;
各种交流滤波电路;
- Product Structure**
Medium: metallized polypropylene film;
Shell: aluminum shell or plastic shell;
Internal potting: resin filling (UL94 V-0);
- Features**
Withstand high Irms current;
Withstand high-frequency working environment: Up to 20kHz;
High reliability, self-healing and long service life;
- Applications**
Used in inverter and frequency converter;
UPS;
Various AC filter circuits;

- 环保节能
- 易安装
- 质量保障
- 寿命长

CBB65 压缩机启动电容

COMPRESSOR STARTING CAPACITOR



- 产品结构**
介质: 金属化聚丙烯薄膜;
外壳: 铝壳封装;
内部灌封: 油填充;
- 特点**
损耗小, 内部温升低;
可靠性高, 有自愈性, 寿命长;
电容量稳定, 内置防爆装置, 使用安全可靠;
- 应用场合**
空调、洗衣机、洗碗机、风机等电器;
各类压缩机的启动和运转;
- Product Structure**
Medium: metallized polypropylene film;
Shell: Aluminium shell package;
Internal potting: oil filling;
- Features**
Low loss and low internal temperature rise;
High reliability, Self-healing property, Long lifetime;
Stable capacitance, built-in explosion-proof device, safe and reliable use;
- Applications**
Air conditioner, washing machine, dishwasher, fan and other electrical appliances;
Starting and running of various compressors;

CBB60 马达启动电容

MOTOR STARTING CAPACITOR



- 产品结构**
介质: 金属化聚丙烯薄膜;
外壳: 塑壳或者铝壳封装;
内部灌封: 树脂填充 (UL94 V-0);
- 特点**
损耗小, 内部温升低;
可靠性高, 有自愈性, 寿命长;
- 应用场合**
洗衣机、卷闸门电机、抽油烟机、碎纸机、水泵等电器;
各类交流电机启动和运转;
- Product Structure**
Medium: metallized polypropylene film;
Shell: Plastic or aluminium shell package;
Internal potting: resin filling (UL94 V-0);
- Features**
Low loss and low internal temperature rise;
High reliability, Self-healing property, Long lifetime;
- Applications**
Washing machine, shutter motor, range hood, paper shredder, water pump and other electrical appliances;
Starting and running of various AC motors;

CBB61 风机启动电容

FAN STARTING CAPACITOR



- 产品结构**
介质: 金属化聚丙烯薄膜;
外壳: 塑壳封装;
内部灌封: 树脂填充 (UL94 V-0);
- 特点**
损耗小, 内部温升低;
可靠性高, 有自愈性, 寿命长;
- 应用场合**
电风扇、换气扇、风机、空气净化器等等;
各类交流电机启动和运转;
- Product Structure**
Medium: metallized polypropylene film;
Shell: Plastic shell package;
Internal potting: resin filling (UL94 V-0);
- Features**
Low loss and low internal temperature rise;
High reliability, Self-healing property, Long lifetime;
- Applications**
Fans, ventilators, air purifiers, etc;
Starting and running of various AC motors;

CD60 马达启动电容

MOTOR STARTING CAPACITOR



- 产品结构**
介质: 铝箔和电解纸;
外壳: 塑壳或者铝壳封装;
内部灌封: 沥青填充;
- 特点**
能够在较低电流下提升扭矩;
安装方便;
- 应用场合**
空调、冷柜、水泵等电器;
各类单相交流电机启动;
- Product Structure**
Medium: Aluminum foil and electrolytic paper;
Shell: Plastic or aluminium shell package;
Internal potting: asphalt filling;
- Features**
Ability to increase torque at low current;
Easy installation;
- Applications**
Air conditioner, refrigerator, water pump and other electrical appliances;
Starting of various single-phase AC motors;

其他电容和材料

OTHER CAPACITORS



DETAILS
CREATE EXCELLENCE
细节 - 成就不凡

